

INDUSTRIAL

PRO SERIES

STAINLESS STEEL

Distributed By:



SPECIFICATIONS

LENGTHS		8', 9', 10', 11'
SHELL CONSTRUCTION		304 stainless steel
FLOOR	2/3 & 3/4 yard 5/7 & 6/8 yard	11 gauge 304 stainless 3/16" 304 stainless
UNDERSTRUCTURE	2/3 & 3/4 yard 5/7 & 6/8 yard	3" A-36 structural steel channel cross members 5" A-36 structural steel channel long members 4" A-36 structural channel cross members 6" A-36 structural channel long members
SIDES		Boxed top rail Sloped rub rail Side board pockets
TAILGATE	2/3 & 3/4 yard	Double acting Manually controlled lever control Laser and flame cut hardware SNAP-LATCH tailgate closing mechanism
BOARD POCKETS		Full height to increase capacities
CAB SHIELD		Contour cut end plates Full height Adjustable for various mounting heights Channel reinforced for increased strength Standard 18" overhang
LIGHTS	5/7 & 6/8 yard	FMVSS 108 lighting with grommets and wiring harness Oval stop/turn/tail lights in rear corner posts
HOIST UNIT		Under body hoist (NTEA Class 60) Scissors hoist (NTEA Class 20, 40 and 50) Direct lift hoist (NTEA Class 10, 20, and 30)

Options:

- Air tailgate
- Coal door(s) in tailgate
- 2, 3, 6 or 9 panel tailgate
- 12", 24", 32" overhang cab shield
- Oval light holes in rear corner posts
- Lighting holes in cab shield front face

	Side Height	Tailgate Height
2/3 yard	13"	19"
3/4 yard	19"	25"
5/7 yard	25"	31"
6/8 yard	31"	39"

Manufacturer reserves the right to change design specifications and furnish products so altered without prior notice.

Caution: The combined weights of the truck chassis, hoist, body and cargo must not exceed the G.V.W.R. of the truck